

Stationary Filtration System Model 265



The Model 265 is designed for kidney-loop filtration of a single machine. With dozens of filter options, you can meet your exact cleanliness goals—as low as 1 μm and 20 ppm water. Each COMO Filter holds up to 20 pounds of dirt and 1 gallon of water, so you can extend fluid life and reduce downtime with fewer filter changes than the competition.

THIS PRODUCT FILTERS

- Hydraulic oil
- Engine oil
- Gear oil
- Lube oil
- Vacuum pump oil
- Turbine oil
- Fire-resistant hydraulic oil
- Transformer oil
- Many other industrial fluids

SPECIFICATIONS

- Two C-1000 chrome-plated depth-filter housings
- 3, 5, or 7 GPM iron gear pump with Buna-N mechanical seals
- 3/4 HP, 115 V, single-phase, 60 Hz, 1725 RPM, TEFC motor
- Freestanding, powder-coated frame
- Dimensions: 24" W x 20" D x 44" H
- Approximate weight: 160 lbs.

STANDARD FEATURES

- Toggle switch motor starter
- Pressure gauge to monitor filter element life
- Frame with bolt holes for floor mounting capability
- Inlet wye strainer to protect pump
- Internal pressure relief in pump
- Stainless-steel element lifters

Don't let particulate & water contamination accelerate fluid breakdown.
Extend fluid life and improve your bottom-line by using a COMO Model 265.