





COMO's Fluid Life Oil Skimmers are the most economical way to keep your water-based fluid reservoirs free of tramp oils and sludge. The slow-rotating wheel is oleophilic, so tramp oils and sludge adhere to the wheel's surface. A spring-loaded wiper blade removes the contaminants and discharges them along a trough into a waste container.

## THIS PRODUCT ELIMINATES

## Tramp oil buildup

- High disposal & replacement costs
- Bacteria and foul
  odors

Increased tool wear

- Unacceptable finish · Contact dermatitis
- . Residual oil on parts
  - Short fluid life

## SPECIFICATIONS

- 115 Volt, 7 RPM, shaded-pole motor & gear assembly
- 12-inch HDPE skimmer wheel for fluids up to 140°F
- ${\boldsymbol{\cdot}}$  Powder-coated skimmer frame and discharge trough
- Approximate dimensions: 14" W x 8" D x 12" H
- Approximate weight: 14 lbs.

## STANDARD FEATURES

- Front- or side-discharge trough
- · High temp stainless-steel skimmer wheel for fluids up to 180°F
- 18-inch HDPE skimmer wheel for fluids up to 140°F
- 18-inch stainless-steel skimmer wheel for fluids up to 180°F

Don't let tramp oils destroy your fluid and stink-up your shop. Extend fluid life and improve part quality by using a COMO Fluid Life Oil Skimmer.

Hubame

Distribuidor autorizado

www.hubame.com.mx | marketing@hubame.com.mx | Teléfono (81) 8000 7600