



LUBRICANTS

Food Machinery Grease

Phillips 66® Food Machinery Grease is a premium quality, food grade, extreme pressure (EP), aluminum complex grease specially developed for the lubrication of machinery in food processing, bottling and packaging plants. It is registered by NSF International as an H1 lubricant for use where incidental food contact may occur, and also meets the requirements of the Canadian Food Inspection Agency (CFIA) for incidental food contact.

Food Machinery Grease is manufactured with high quality base oils and thickened with an aluminum complex soap. It is compounded with special food grade additives to provide excellent EP and antiwear properties, excellent oxidation resistance and good adhesion to metal surfaces. It has excellent resistance to water washout and provides excellent rust and corrosion protection in applications where the equipment is exposed to fruit acids, chemicals, or saline solutions.

Applications

- Food processing equipment in canneries, meat packing plants and poultry plants
- Bottling plants
- Seammers

Food Machinery Grease meets the requirements of the following government

and industry specifications:

- Canadian Food Inspection Agency (CFIA) requirements for incidental food contact (LONO)
- FDA 21 CFR 178.3570 for incidental food contact
- NSF International H1 and former 1998 USDA H1 guidelines for incidental food contact (NSF Registration No. 142471)
- U.S. EPA/U.S. Coast Guard Static Sheen Test, Federal Register Vol. 58, No.41

Features/Benefits

- Excellent oxidation resistance
- Excellent resistance to water washout
- Good extreme pressure and antiwear properties
- Protects against rust and corrosion
- Good adhesion to metal surfaces
- Non-staining
- Suitable for use over a wide range of operating temperatures

Note: Aluminum complex greases have an inherent tendency to bleed a small amount of oil during storage. Containers of Food Machinery Grease should be stored in a temperature controlled environment to minimize oil separation.

Food Processing
Machinery
Extreme Pressure
Aluminum
Complex Grease
NSF H1
Registered



Hubame

Distribuidor autorizado

www.hubame.com.mx | marketing@hubame.com.mx | Teléfono (81) 8000 7600



LUBRICANTS

Food Machinery Grease

| Typical Properties | | |
|---|------------|------------------|
| NLGI Grade | | 2 |
| Thickener Type | | Aluminum Complex |
| Color | | White |
| Texture | | Smooth / Tack y |
| Density, lbs/gal | | 7.86 |
| Dropping Point, °C (°F) | ASTM D2265 | 260 (500) |
| Viscosity, Kinematic | ASTM D445 | |
| Viscosity @ 40°C, cSt | | 222 |
| Viscosity @ 100°C, cSt | | 27.2 |
| Penetration, Worked (60 strokes) | ASTM D217 | 26.5 - 29.5 |
| Oxidation Stability, 100 Hours, psi (kPa) | ASTM D942 | 5 (34.5) |
| Four-Ball Wear Scar, mm | ASTM D2266 | 0.55 |
| Four-Ball EP, Weld Load, Kg | ASTM D2596 | 500 |
| Timken OK Load, lbs | ASTM D2509 | 40 |
| Corrosion Prevention | ASTM D1743 | Pass |
| Copper Corrosion | ASTM D4048 | 1b |
| Water Spray-off, wt% | ASTM D4049 | 27.5 |

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/SDS>.

01-2019

Hubame

Distribuidor autorizado

www.hubame.com.mx | marketing@hubame.com.mx | Teléfono (81) 8000 7600