





The Model 122 fits four COMO Filters, giving it the filtration capacity needed for large reservoirs while maintaining 1 µm particle and 20 ppm water performance. Each COMO Filter holds up to 20 pounds of dirt and 1 gallon of water, so you can extend fluid life and reduce downtime with fewer filter changes than the competition.

#### THIS PRODUCT FILTERS

#### Hydraulic oil

- Gear oil
- Lube oil
- Turbine oil
- Transformer oil
- Engine oil
- Vacuum pump oil
- Fire-resistant hydraulic oil
- Many other industrial fuids

### SPECIFICATIONS

- Two C-1002 chrome-plated depth-filter housings
- •7, 11, or 15 GPM iron gear pump with Buna-N mechanical seals
- 3/4 or 1 HP, 115 V, single-phase, 60 Hz, 1725 RPM, TEFC Motor
- · Portable, chrome-plated frame with oil-resistant wheels
- Dimensions: 23" W x 24" D x 60" H
- · Approximate weight: 230 lbs.

#### STANDARD FEATURES

- · Pressure switch with high/low shut-off for unattended operation
- · Fluid transfer feature to bypass depth-filter housings
- · Gate valve for flow control
- Motor starter with thermal overload protection
- Power and pump indicator lights
- Pressure gauge to monitor filter element life
- · Inlet wye strainer to protect pump

Don't let particulate & water contamination affect production. Reduce downtime and maximize productivity by using the COMO Model 122.

# Hubame

Distribuidor autorizado

## www.hubame.com.mx | marketing@hubame.com.mx | Teléfono (81) 8000 7600